

Lyman, Me. – Town Roads.  
Paving Spec/Bid Form

September 13, 2021

WIDTH: **20-22'**

LENGTH: **5780 +/-**

Reclaim with cement stabilization and fine grade.  
¾" crushed concrete or ¾" reclaim for shoulders  
Find grading to be done by contractor.  
Contractor will provide water truck and roller.  
All traffic control will be provided by contractor.

Reclaimed \_\_\_\_\_ Reclaim minimum 8" below surface  
Per sq. yard \_\_\_\_\_  
**PERCENT OF CEMENT IN THE RECLAIM STABILIZATION – 4%**

**BASE PAVEMENT**

2 ½ IN. – 19.0 MM – HMA MDOT

Fine grading to be done by contractor on reclaim areas. Surface pavement shall be 1-1/2" 9.5MM MDOT

All virgin materials in mix. All traffic control will be provided by contractor.

**PRICE PER TON: for 19 MM** \_\_\_\_\_ **Price per ton: for 9.5MM** \_\_\_\_\_  
**TOTAL TONNAGE: of each** \_\_\_\_\_

**TOTAL PRICE:** \_\_\_\_\_

**2 ft SHOULDERS TO BE COMPACTED**

**Material to be ¾" crushed concrete or ¾" reclaim**

**PER LINEAL FOOT:** \_\_\_\_\_

**TOTAL BID PRICE:** \_\_\_\_\_

**NAME:** \_\_\_\_\_ **PHONE:** \_\_\_\_\_

**TITLE:** \_\_\_\_\_ **Cell:** \_\_\_\_\_

**ADDRESS:** \_\_\_\_\_ **Fax:** \_\_\_\_\_

\_\_\_\_\_ **E-mail:** \_\_\_\_\_